




The Urban Range Sliding/Stacking Door



CAPRAL
ALUMINIUM

urban

Flexible and versatile in design, sliding/stacking doors can be manufactured to specific requirements, whether it be a 2, 3 or 4 panel standard sliding/stacking door or 3 and 6 panel sliding/stacking door. Suitable for both residential or apartment living, they are perfect for alfresco living, providing an abundance of natural light and giving a feeling of space. High quality rollers allow ease of sliding for all panels and quality door locks will give you peace of mind in the security of your home. These doors can also be integrated with insect or security screens.

The Urban Sliding/Stacking Door




The new Urban Sliding/Stacking Door offers a high degree of design flexibility. Complemented with high quality hardware plus excellent structural and weather performance, the Urban Sliding/Stacking Door has been designed to suit Australia's wide range of climatic conditions. Integrated insect or barrier screening options and double glazing capabilities ensure the Urban Sliding/Stacking Door can be tailored to your exacting requirements.



As part of the Capral Urban Residential Range, it can be integrated with a complementary selection of sliding, casement, awning and double hung windows to provide a total window solution.

Features and Benefits:

- 101.6mm Framing System
- Single and double glazed options
- Standard configurations (XO, OXO and OXXO)
- Multistack configurations (XXO or OXXXXO)
- Inside and outside corner configurations (OXXcXXO)
- Dedicated double glaze sections
- Highlight option available on selected configurations
- Standard and low profile sill options
- Self draining sill design
- Integrated insect and security screening options
- Custom design hardware options
- Standard and mortice lock options
- Cavity slider options
- Corner sliding configuration options

Finishes Available:

-  Powder coated range
-  Anodised Aluminium
-  Woodgrain



	584 Sliding Door	584 Stacking Door
Maximum Recommended Panel Sizes		
Height	2700mm	2700mm
Width	1200mm STD 1500mm HD	1200mm STD 1500mm HD
Weight	160kg	160kg
Frame Dimensions (Depth & Height)		
Option 1 Sill	101.6 x 50 STD	101.6 x 50mm STD
Option 2 Sill	101.6 x 62 HP	101.6 x 19mm LP
Maximum Product Performance		
SLS (Pa)	2500	3000
ULS (Pa)	6000	5500
WATER (Pa)	450	300
Glazing Details		
Single Glazed	4mm - 10mm	4mm - 10mm
Double Glazed	16mm & 18mm	16mm - 18mm
Maximum Acoustic Rating		
Rw	30	53*
C _v CTR	-1; -2	-2; -7
Compatible with		
Urban Residential Range		
AGS Commercial Range		

* Secondary glazed configurations.
Please refer to Capral technical documentation for full product specifications.

CAPRAL
ALUMINIUM

1800 ALUMINIUM (258 646)
www.capral.com.au
Capral Limited ABN 78 004 213 692 | May 2016